

Class 1

Flexi-Seal P.U.D. - Flexible Waterproofing Membrane

Product Disclosure Information Self-Assessment

Version: V1 08.08.23

Product name	Flexi-Seal P.U.D. - Flexible Waterproofing Membrane
Product line	
Product identifier	AW.FLEXI.PUD

Product description

Flexi-Seal PUD is a light blue, water-based polyurethane modified flexible waterproofing membrane.

Flexi-Seal does not require the use so any reinforcement, and is for waterproofing of shower recesses, bathrooms, laundries, balconies and decks.

Also used as the key component of a modified system for specialized secondary containment in the health and aged care industries.

It can be used in both internal and external waterproofing applications, over concrete, render, block work, fiber cement, Gyprock, plywood and particle board surfaces.

Part of the Flexi-Seal waterproofing system, in conjunction with Universal Primer, Butylseal and Bondlast ceramic tile adhesives

Relevant building code clauses

B2 Durability — B2.3.1 (a)

E2 External moisture — E2.3.2, E2.3.3, E2.3.7

F2 Hazards building materials — F2.3.1

Contributions to compliance

B2.3.1 (b) (ii) and B2.3.2 Flexi-Seal PUD has durability so at least 15 years when installed by an Approved Applicator.

E2.3.1, E2.3.2, E2.3.3, E2.3.4, E2.3.5, E2.3.6. Flexi-Seal PUD when installed by an Approved Applicator as part so the Licensed waterproofing system along with Universal Primer and Butylseal tape provides an

impervious and easily cleaned barrier.

F2.3.1 Flexi-Seal PUD meets this requirement and will not present a health hazard to people

Scope of use

Flexi-Seal PUD is manufactured for use as part of a licensed waterproofing system that includes Universal Primer & Butylseal tape.

For use on floors and walls in showers, bathrooms, laundries, balconies' & decks.

Conditions of use

Preparation: • All areas to be waterproofed must be clean and dry, free of grease, oil and paint and all loose materials, as well as any other contaminants. • Concrete should be allowed to cure for a minimum of 28 days prior to application to waterproofing. • Sheet and timber substrates must be installed and fixed in accordance with the manufacturer's specifications. • Prior to application, surfaces (in particular porous substrates) should be primed with Universal Primer.

Application: • Flexi-Seal PUD is a Class III Membrane. Care must be taken in any immediate wet areas such as shower recesses. • Wall-to-wall and wall-to-floor junctions require a bond breaker mechanism applied prior to the application of Flexi-Seal PUD. A neutral cure silicone is recommended. The bond breaker must be applied in accordance with AS/NZS 3740: 2004 Class III Wet Area Membranes. • Should a tape be required on the junctions, use 80mm Butylseal Tape. Apply a wider 150mm Butylseal Tape over the trap area after it has been primed, and turn it down into the trap to help better secure the waste trap area. • Apply the first coat of Flexi-Seal PUD to the overall pre-primed substrate areas, ensuring an even coverage using a brush, roller or airless spray. • Allow to dry before applying a second, heavier coat at 90° to the first. Ensure complete coverage is achieved and no air bubbles exist. • Apply a third coat if imperfections are present in the membrane. • Ensure each coat has fully cured prior to application of additional coats. • Average dry film thickness should be approximately 1mm, and should not be any less than 0.75mm.

Flexi-Seal PUD must be installed by an Approved Applicator.

Supporting documentation

The following additional documentation supports the above statements:

Title (type)	Version	URL
Flexi-Seal PUD Technical Data Sheet (Installation)	V1.2023	https://0010019.expert.services/systems/waterproofing/
Flexi-Seal Licensed Waterproofing System - BRANZ Appraisal (Certification)	#475 (2019) Exterior	https://bsndlast.cs.nz/waterproofing/BRANZ_475
Flexi-Seal Licensed Waterproofing System - 15 Year Warranty (Warranty)		https://bsndlast.cs.nz/waterproofing/15yrWarranty

Contact details

Manufacture location	Overseas
Legal and trading name of manufacturer	RLA Polymers PTY Ltd
Legal and trading name of importer	DGL Manufacturing Limited T/A DGL Bondlast
Importer address for service	24-28 Lady Ruby Drive Auckland 2013
Importer website	www.bondlast.co.nz
Importer NZBN	9429032804584
Importer email	Sales.bondlast@dglgroup.com
Importer phone number	092672772

Warnings and bans

Is the building product/building product line subject to warning or ban under section 26 so the Building Act 2004?

Ns

Appendix

BPIR Ready selections

Category: Tanking and damp proof membranes

Building code performance clauses

All relevant building code performance clauses listed in this document:

B2 Durability

B2.3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser so the *specified intended life so the building*, io stated, or:

- (a) the life so the building, being not less than 50 years, is:
 - i. those *building elements* (including floors, walls, and fixings) provide structural stability to the *building*, or
 - ii. those *building elements* are difficult to access or replace, or
 - iii. failure of those *building elements* to comply with the *building code* would go undetected during both normal use and maintenance so the building

E2 External moisture

E2.3.2

Roofs and exterior walls must prevent the penetration of water that could cause undue dampness, damage to *building elements*, or both.

E2.3.3

Walls, floors, and structural elements in contact with, or in close proximity to, the ground must not absorb or transmit moisture in quantities that could cause undue dampness, damage to *building elements*, or both.

E2.3.7

Building elements must be constructed in a way that makes due allowance for the following:

- a. the consequences so failure:
- b. the effects of uncertainties resulting form *construction* or from the sequence in which different aspects of *construction* occur:
- c. variation in the properties so materials and in the characteristics so the site.

F2 Hazardous building materials

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the *construction so buildings*, shall not give rise to harmful concentration at the surface of the material where the material is exposed, or in the atmosphere so any space.

Characteristics:

- Flexi-Seal PUD is a light blue, water-based polyurethane modified flexible waterproofing membrane.
- It is fast drying and UV stable, and can be recoated in as little as 4 hours in optimal conditions.
- Flexi-Seal does not require the use of any reinforcement, and is ideal for waterproofing of shower recesses, bathrooms, laundries, balconies and decks.
- It can be used in both internal and external waterproofing applications, over concrete, render, block work, fibre cement, gyprock, plywood and particle board surfaces.
- Easy to clean in water.
- Part of the Flexi-Seal waterproofing system, in conjunction with Universal Primer, Butylseal, and Bondlast ceramic tile adhesives



Part of the

Flexi-SEAL
Licensed waterproofing system

Preparation:

- All areas to be waterproofed must be clean and dry, free of grease, oil and paint and all loose materials, as well as any other contaminants.
- Concrete should be allowed to cure for a minimum of 28 days prior to application of waterproofing.
- Sheet and timber substrates must be installed and fixed in accordance with the manufacturer's specifications.
- Prior to application, surfaces (in particular porous substrates) should be primed with Universal Primer.

Application:

- Flexi-Seal PUD is a Class III Membrane. Care must be taken in any immediate wet areas such as shower recesses.
- Wall-to-wall and wall-to-floor junctions require a bond breaker mechanism applied prior to the application of Flexi-Seal PUD. A neutral cure silicone is recommended. The bond breaker must be applied in accordance with AS/NZS 3740: 2004 Class III Wet Area Membranes.
- Should a tape be required on the junctions, use 80mm Butylseal Tape. Apply a wider 150mm Butylseal Tape over the trap area after it has been primed, and turn it down into the trap to help better secure the waste trap area.
- Apply the first coat of Flexi-Seal PUD to the overall pre-primed substrate areas, ensuring an even coverage using a brush, roller or airless spray.

- Allow to dry before applying a second, heavier coat at 90° to the first. Ensure complete coverage is achieved and no air bubbles exist.
- Apply a third coat if imperfections are present in the membrane.
- Ensure each coat has fully cured prior to application of additional coats.
- Average dry film thickness should be approximately 1mm, and should not be any less than 0.75mm.

Cleanup:

- Clean all equipment with water after use.

Packaging/Shelf Life:

- Flexi-Seal PUD can be stored for up to 12 months in an unopened container.
- Store in a dry area above ground, out of direct sunlight.
- Flexi-Seal PUD is available in 4L and 15L packaging.

Coverage:

- Flexi-Seal PUD will cover approximately 12m² per 15L pail in internal applications and 10m² per 15L pail in external applications

Notes:

- A Material Safety Data Sheet is available upon request.

Disclaimer: The information supplied is to the best of our knowledge true and accurate. The actual application of the product is beyond the manufacturer's control. Any failure or damage caused by the incorrect usage of the product is not the responsibility of the manufacturer. The manufacturer insists that all workmanship must be carried out in accordance with AS 3958.1-2007. It is also the responsibility of the end user to ensure that the literature in their possession is the latest issue.

SAFETY DATA SHEET

Page 1 of 3

Product: **FLEXISEAL P.U.D.**

Issue Date: 29.03.2021

Issued by Bondlast

Classified as non-hazardous

SECTION 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: FLEXISEAL P.U.D
Product code: AW.FLEXI.PUD
Recommended Use: Wet area waterproofing membrane
Company Name: DGL Bondlast
Address: 24 – 28 Lady Ruby Drive, East Tamaki. Auckland 2013, New Zealand.
Phone / Fax: (09) 267 2772 **Fax:** (09) 268 0305 Available Monday – Friday 8.00am – 5.30pm.

Emergency Phone: New Zealand Poisons Centre: 0800 764 766

SECTION 2. HAZARDS IDENTIFICATION

Hazard NON-HAZARDOUS CHEMICAL.
Classification: NON-DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.
Signal Word: Not applicable
Hazard Statements **Aggravated medical conditions caused by exposure.**
Ingestion: May cause abdominal discomfort, nausea and vomiting.
Eye: May cause soreness. A mild irritant.
Skin: Repeated or prolonged skin contact may lead to irritation.
Inhalation: Prolonged use in poor ventilation may cause irritation to the nasal passages.
Chronic Effects: No long term exposure symptoms are known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical characterisation: Blue liquid

Ingredients:	<u>Name</u>	<u>CAS</u>	<u>Proportion</u>
	Calcium Carbonate	1317-65-3	10 - 40%
	Acrylic Copolymer	Proprietary	30 - 50%
	Polyurethane elastomer	Proprietary	0 - 20%
	Other Non Hazardous Ingredients	–	20 - 40%

SECTION 4. FIRST AID MEASURES

Eye: Flush with water. Seek medical advice if irritation or other symptoms persist.
Swallowed: Do NOT induce vomiting. Take water or milk and seek medical advice if any symptoms or discomfort is evident.
Skin: Wash with water. Seek medical advice if irritation or other symptoms persist.
Inhaled: Remove to fresh air. Seek medical advice if irritation or other symptoms persist.
First aid facilities: Ensure availability of clean water to wash eyes or skin.
Advice to Doctor: Treat symptomatically.

SAFETY DATA SHEET

Page 2 of 3

Product: **FLEXISEAL P.U.D.**

Issue Date: 29.03.2021

Issued by Bondlast

Classified as non-hazardous

SECTION 5. FIRE FIGHTING MEASURES

Extinguisher: All extinguishing media can be used. Material will not ignite readily.

Special protective precautions and equipment for fire fighters: Fire fighters to wear self-contained breathing apparatus if risk of exposure to products of decomposition.

Specific Hazards: Non-flammable in the wet state but dried product will burn if ignited.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures: Contain - prevent contamination of drains and waterways.

Spills and Disposal: Caution should be taken to avoid spills. Spills on floor can be slippery. Clean up spills immediately. Spills should be cleaned up with water and mop. Large spills should be contained, transferred to sealed containers and disposed of as non-toxic liquid waste.

Environmental Precautions: Notify authorities if product enters sewers or public waterways.

SECTION 7. HANDLING AND STORAGE

Conditions for safe storage including any incompatibilities: Store in original containers. Store in a cool dry place, undercover away from sunlight. Store away from oxidizing agents and acids.

Handling: Always use protective gloves and clothing when handling.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

National Exposure Standards: Natural ventilation should be adequate when used as directed. Safety glasses, goggles or faceshield as appropriate.

Personal Protection

Respirator: PVC or rubber gloves.

Eyes: Overalls or similar protective apparel.

Glove Type: Enclosed footwear.

Clothing: Wash hands after use and before eating, drinking, smoking or using toilet

Footwear:

Work/Hygienic:



No exposure standards have been established for this product. However, as with all chemicals, exposure should be limited as much as possible.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: pH value:

Odour: Flammability:

Boiling Point: VOC:

Solubility in water: Viscous Blue Liquid.

Specific Gravity:

Slight characteristic odour. < 100°C. Soluble. Approx 1.2
Approx 8.5.
Not Flammable.
< 2g

SAFETY DATA SHEET

Page 3 of 3

Product: **FLEXISEAL P.U.D.**

Issue Date: 29.03.2021

Issued by Bondlast

Classified as non-hazardous

SECTION 10. STABILITY AND ACTIVITY

Chemical Stability: This product is water based and stable under most conditions.
On exposure to high temperature, may decompose, releasing toxic gasses.

Incompatible

Materials: None known

Hazardous

Polymerization: Will NOT occur.

SECTION 11. TOXICOLOGICAL INFORMATION

Chronic Effects: Not Available – refer to Section 2 Hazards Identification.

SECTION 12. ECOLOGICAL INFORMATION

Mobility: Disperses in water
Environ. Protection: Avoid contaminating waterways.

SECTION 13. DISPOSAL CONSIDERATIONS

Waste Disposal: Dispose to licensed disposal contractor in accordance with local regulations.
Product Disposal: Dispose to licensed disposal contractor in accordance with local regulations.
Container Disposal: Dispose as industrial waste.

SECTION 14. TRANSPORT INFORMATION

Transport Information: Not classified as dangerous.
NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS: Land, Air or Sea.
HAZCHEM: Not Applicable
Marine Pollutant: No

SECTION 15. REGULATORY INFORMATION

Poisons Schedule: Not scheduled

SECTION 16. OTHER INFORMATION

Date of preparation: 29.03 2021
Literature references: MSDS's for individual raw materials
Abbreviations:
CAS No. Chemical Abstract Service Registry
TWA Threshold limit value

Safety data sheets are updated regularly; please ensure that you have a current copy.

The information contained herein is based on data considered accurate and reliable to the best of our knowledge and belief as of the date compiled. No warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use hereof. DGL Bondlast assumes no responsibility for personal injury or property damage to vendors, users or third parties caused by this material. Such users or vendors assume all risks associated with the use of this material. It is the users responsibility to satisfy themselves as to the suitability and completeness of the information for their particular use. The users must determine whether the use of the information and data is in accordance with local laws and regulations.

End of SDS

UNIVERSAL PRIMER

RAPID DRYING ACRYLIC PRIMER

Characteristics:

- Universal Primer is a rapid drying, solvent-free, low VOC, water-based acrylic primer.
- Universal Primer is formulated to assist adhesive and waterproofing bonding on surfaces that might otherwise cause issues.
- It is intended for use over porous and non-porous substrates, such as existing tiles, old paint (with the exception of oil-based paints), vinyl adhesive, vinyl tile, carpet adhesive residue, metal, and sealed or burnished concrete floors.
- Universal Primer is compatible with cement-based ceramic tile adhesives.
- It can be applied both internally and externally over clean and dry surfaces.

Preparation:

- Ensure surface is clear of oil, grease and wax.
- All loose materials (e.g. dust, etc) must be removed prior to applying Universal Primer.
- Concrete floors must be dry in accordance with A.S. 3958.1-2007
- Where the temperature is less than 5°C or greater than 30°C, contact DGL Bondlast for technical advice.
- Thoroughly mix primer prior to use.

Application:

On Porous Substrates:

- Dilute Universal Primer using 4 parts clean water to 1 part Universal Primer.
- Apply primer using a roller, brush or broom, ensuring entire area is completely primed.
- Very absorbent concrete may require a second coat of Universal Primer diluted the same as the first coat.
- Allow to cure for 30 minutes @ 20°C.

On Non-Porous Substrates:

- Apply an even layer of undiluted Universal Primer.
- Allow to cure for 2 hours @ 20°C

Once Universal Primer has dried to a clear, tack-free film, adhesive or waterproofing membranes may be applied to the surface.



Part of the

Flexi-SEAL
Licensed waterproofing system

Cleanup:

- Clean all equipment with water after use.

Packaging/Shelf Life:

- Universal Primer can be stored for 12 months in a sealed container.
- Store in a dry area above ground, out of direct sunlight.
- Universal Primer is available in 1L, 5L, and 20L packaging.

Coverage:

Universal Primer will cover approximately:

- 8m² per litre **undiluted**.
- 30m² per litre **diluted 1:4 with water**.

Notes:

A Material Safety Data Sheet is available upon request.

- Do not apply on substrates subject to rising damp.
- Do not apply at a thickness greater than 1mm.
- Do not apply on tiles with wax or excessive gloss coating.

Disclaimer: The information supplied is to the best of our knowledge true and accurate. The actual application of the product is beyond the manufacturer's control. Any failure or damage caused by the incorrect usage of the product is not the responsibility of the manufacturer. The manufacturer insists that all workmanship must be carried out in accordance with AS 3958.1-2007. It is also the responsibility of the end user to ensure that the literature in their possession is the latest issue.

SAFETY DATA SHEET

SECTION 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: Universal Primer
Other Names: RL7167
Recommended Use: Primer
Company Name: DGL Bondlast
Address: 24 – 28 Lady Ruby Drive East Tamaki, Auckland.
Other information: Manufactured at RLA Polymers NZ Ltd
Tel/Fax: Tel: (09) 267 2772

NZ Contact: DGL Bondlast
Address: 24 – 28 Lady Ruby Drive East Tamaki, Auckland, New Zealand.
Phone: (09) 267 2772 **Fax:** (09) 268 0305
Emergency Telephone: (09) 267 2772 Available Monday – Friday 8.00am – 5.30pm.
New Zealand Poisons Centre: 0800 764 766

SECTION 2. HAZARDS IDENTIFICATION

Hazard Classification: Classified as non hazardous according to criteria of Worksafe Australia and New Zealand

NON HAZARDOUS according to NZ HSNO Regulations
Not Regulated under NZ5433 for land transportation

Risk Phrases

Safety Phrases

Substance Classification

Hazard Statements

Aggravated medical conditions caused by exposure.

Swallowed: No adverse affects expected.

Eye: May cause mild irritation to the eyes.

Skin: May cause irritation to the skin.

Inhaled: May cause irritation to the nasal passages.

Advice to doctor: Treat symptomatically

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	%	CAS No	TWA
Acrylic Co-Polymer	50 – 90%	None allocated	None Established
Water	20 – 50%	None allocated	None Established
Ingredients	< 10%	Various	None Established

SECTION 4. FIRST AID MEASURES

Eye: Flush/rinse eyes with plenty of water for at least 15 minutes.

Swallowed: Wash mouth and lips with water. DO NOT induce vomiting.
Give water to dilute stomach contents. Seek medical attention if

symptoms persist.

Skin:

Wash affected area thoroughly with water.

Inhaled:

Unlikely to be an inhalation risk but remove from point of exposure to fresh air.

UNIVERSAL PRIMER

Version Number: 3

May 2020

Page 2 of 4

SAFETY DATA SHEET

SECTION 5. FIRE FIGHTING MEASURES

Extinguisher: All extinguishing media can be used.

Hazards from Combustion products: On exposure to high temperature, may decompose, releasing toxic gases.

Special protective precautions and equipment for fire fighters:

Hazchem Code: None Allocated

Flash Point: None Allocated

Fire/Explosion Hazard Limit	Auto Ignition Temp	Lower Explosion Limit	Upper Explosion Limit
	n/a	n/a	n/a

SECTION 6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures: Keep spectators away and avoid breathing vapours.

Methods and Materials for Containment and Clean up –

Spills and Disposal: Clean up any spills as soon as possible. Soak up with sand then shovel up and place in suitable container and allow to dry for disposal. Only dispose of at approved disposal sites. Follow local regulations.

Environmental Precautions: Notify authorities if product enters sewers or public waterways.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling: Avoid damaging containers. Keep lids on containers when not in use.

Conditions for safe Storage including any incompatibilities:

Store in a cool dry place, undercover away from moisture.

Storage Temperatures: Min 0 degC Max 40 degC.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

National Exposure Standards for mixture: No exposure standards standard has been established for this product.

Personal Protection:

Respirator Type Not required. Use in a well ventilated area

Eyes Safety eyewear with splash guards or side shields to prevent eye contact is recommended.

Glove Type	Wear protective rubber gloves.
Clothing	Wear protective overalls.
Footwear	Wear safety boots.
Work/Hygienic	Wash hands and other exposed areas with soap and water before eating, drinking and smoking. Use barrier cream to protect skin.

UNIVERSAL PRIMER

Version Number: 3

May 2020

Page 3 of 4

SAFETY DATA SHEET

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Green viscous liquid.
Solubility in water: Soluble
pH: 7.5 – 8.5

SECTION 10. STABILITY AND ACTIVITY

Chemical Stability: Product is considered stable under normal storage and handling conditions.
Conditions to avoid: Freezing, excessive heat and fluctuating temperatures.
Incompatible Materials:
Hazardous Decomposition Products: Oxides of carbon
Hazardous Reactions: None known.

SECTION 11. TOXICOLOGICAL INFORMATION

No data available for this material – refer to individual raw materials.

SECTION 12. ECOLOGICAL IDENTIFICATION

Do not allow this product to enter the environment – in particular waterways. Will biodegrade in waterways and not classed as an eco-toxin, however even small quantities will show as a white haze until well diluted.
No specific data available for this product.

SECTION 13. DISPOSAL CONSIDERATIONS

Special precautions for landfill or incineration:
Consult manufacturer for recycling options and recycle where possible.
Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

SECTION 14. TRANSPORT INFORMATION

UN Number: None allocated
UN Proper Shipping:
Subsidiary Risk

Poison schedule: None allocated
allocated

HAZCHEM Code: None

Packing Group: None allocated

DG Class: None allocated

SECTION 15. REGULATORY INFORMATION

Group Standard: Not applicable
Approved Handler: Not required

UNIVERSAL PRIMER

Version Number: 3

May 2020

Page 4 of 4

SAFETY DATA SHEET

SECTION 16. OTHER INFORMATION

Date of preparation: 28th May 2020
Literature references: MSDS's for individual raw materials
Abbreviations:
CAS No Chemical Abstract Service Registry
TWA Threshold limit value

Safety data sheets are updated regularly; please ensure that you have a current copy.

The information contained herein is based on data considered accurate and reliable to the best of our knowledge and belief as of the date compiled. No warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use hereof. DGL Bondlast assumes no responsibility for personal injury or property damage to vendors, users or third parties caused by this material. Such users or vendors assume all risks associated with the use of this material. It is the users responsibility to satisfy themselves as to the suitability and completeness of the information for their particular use. The users must determine whether the use of the information and data is in accordance with local laws and regulations.

End of MSDS

BUTYL SEAL TAPE - TDS

Characteristics:

- Butylseal Tape is a grey butyl rubber tape with excellent elongation properties and a degree of memory.
- Butylseal does not shrink and is permanently flexible.
- It is non-soluble and waterproof.
- Butylseal can be painted and plastered over.
- Designed for use on timber, plywood, fibre cement, concrete, masonry block, gib board, most metals, steel and plastic roofing, plastic sheet wall linings, glass and fibreglass.
- Recommended for use within waterproofing and floor levelling systems.

Preparation:

- Surfaces must be free of oil, grease, wax, curing compounds, dust, old adhesives and any other contaminants that may inhibit bonding.
- Surfaces should be dry and not subject to excessive movement.
- Ensure all concrete surfaces have had sufficient cure time, and that all other surfaces and products are fixed in accordance to the manufacturer's specifications and relevant standards.
- It is recommended that surfaces are primed with Universal Primer prior to application.

Application:

- Place Butyl tape in place, ensuring any joins are overlapped a minimum of 50mm.
- Apply pressure to tape to ensure it is well bonded to substrate.
- Apply pressure to joints with a roller to join mould laps together and confirm tape adhesion.

Cleanup:

- Scrape excess Butylseal Tape off substrate and dispose.
- Clean tools and surfaces if necessary with a solvent, ensuring correct protective equipment is used.

Packaging/Storage:

- Butylseal Tape has an indefinite life when stored correctly.



Part of the
Flexi-SEAL
Licensed waterproofing system

-
- Store in a dry area, above ground and out of direct sunlight.
 - Do not store in areas above 40°C.
 - Butylseal Tape single-sided (woven backing) is available in 80mm, 150mm, 500mm widths, in 15m rolls.
 - Butylseal Strip Tape is available in 25mm x 37m rolls.
 - Butylseal Manhole Sealant is available in 15mm x 3.81m rolls.

Butylseal Corners are available for both internal and external joints.

Attributes:

- Butylseal Tape is a smooth grey rubber mastic tape.
- Butylseal Tape will deform under compression.
- Butylseal may be applied from 0°C to 40°C.
- Butylseal will remain serviceable from -20°C to 80°C.
- Butylseal has up to 400% elongation at break.

Notes:

- A Material Safety Datasheet is available at request.
-