

UNIVERSAL PRIMER

RAPID DRYING ACRYLIC PRIMER

Characteristics:

- Universal Primer is a rapid drying, solvent-free, low VOC, water-based acrylic primer.
- Universal Primer is formulated to assist adhesive and waterproofing bonding on surfaces that might otherwise cause issues.
- It is intended for use over porous and non-porous substrates, such as existing tiles, old paint (with the exception of oil-based paints), vinyl adhesive, vinyl tile, carpet adhesive residue, metal, and sealed or burnished concrete floors.
- Universal Primer is compatible with cement-based ceramic tile adhesives.
- It can be applied both internally and externally over clean and dry surfaces.

Preparation:

- Ensure surface is clear of oil, grease and wax.
- All loose materials (e.g. dust, etc) must be removed prior to applying Universal Primer.
- Concrete floors must be dry in accordance with A.S. 3958.1-2007
- Where the temperature is less than 5°C or greater than 30°C, contact RLA Polymers NZ Ltd for technical advice.
- Thoroughly mix primer prior to use.

Application:

On Porous Substrates:

- Dilute Universal Primer using 4 parts clean water to 1 part Universal Primer.
- Apply primer using a roller, brush or broom, ensuring entire area is completely primed.
- Very absorbent concrete may require a second coat of Universal Primer diluted the same as the first coat.
- Allow to cure for 30 minutes @ 20°C.

On Non-Porous Substrates:

- Apply an even layer of undiluted Universal Primer.
- Allow to cure for 2 hours @ 20°C

Once Universal Primer has dried to a clear, tack-free film, adhesive or waterproofing membranes may be applied to the surface.

Cleanup:

- Clean all equipment with water after use.



Part of the

Flexi-SEAL
Licensed waterproofing system

Packaging/Shelf Life:

- Universal Primer can be stored for 12 months in a sealed container.
- Store in a dry area above ground, out of direct sunlight.
- Universal Primer is available in 1L, 5L, and 20L packaging.

Coverage:

Universal Primer will cover approximately:

- 8m² per litre **undiluted**.
- 30m² per litre **diluted 1:4 with water**.

Notes:

A Material Safety Data Sheet is available upon request.

- Do not apply on substrates subject to rising damp.
- Do not apply at a thickness greater than 1mm.
- Do not apply on tiles with wax or excessive gloss coating.

Disclaimer: The information supplied is to the best of our knowledge true and accurate. The actual application of the product is beyond the manufacturers control. Any failure or damage caused by the incorrect usage of the product is not the responsibility of the manufacturer. The manufacturer insists that all workmanship must be carried out in accordance with AS 3958.1-2007. It is also the responsibility of the end user to ensure that the literature in their possession is the latest issue.



RLA Polymers NZ Ltd
24 – 28 Lady Ruby Drive
East Tamaki
Auckland 2013
New Zealand

SOLUTIONS FOR INDUSTRY

Phone: (09) 267 2772
Fax: (09) 268 0305
Email: sales@rlapolymers.co.nz
Web: www.rlapolymers.co.nz